

Table of Contents

glite-ce-job-list.....	1
NAME.....	1
SYNOPSIS.....	1
DESCRIPTION.....	1
OPTIONS.....	1
EXIT STATUS.....	2
EXAMPLES.....	2
SEE ALSO.....	2
Index.....	2

glite-ce-job-list

Section: User Commands (1)

Index

NAME

glite-ce-job-list - Displays the Ids of all the jobs, belonging to the user issuing the command, which are ``known" to a specified CREAM based CE.

SYNOPSIS

glite-ce-job-list [options] <host>[:<port>]

DESCRIPTION

glite-ce-job-list is the command to get the identifiers of all the jobs owned by the user issuing the command, which have been submitted to the CREAM based CE whose host and port number are specified as argument of the command. If the port is not specified, the port to be used is the one specified in the CREAM UI configuration file.

These returned CREAM job identifiers can be later used as a handle to perform monitor and control operations on the jobs.

It is possible to redirect the returned CREAM jobIds into an output file using the --output (-o) option. If the file already exists and it is not a CREAM id file, the user is asked if she wants to overwrite the file, or if she prefers to abort the operation.

OPTIONS

--help, -h

Displays command usage.

--conf file_name, -c file_name

Specifies the user specific configuration file.

--donot-verify-ac-sign, -A

Allows the execution of the command even if the VO voms server certificate is not installed.

--output file_name, -o file_name

Writes the resulting jobIds in the file specified by file_name. file_name can be either a simple name or an absolute path on the submitting machine. In the former case the file file_name is considered in the current working directory.

--nomsg, -n

This option makes the command print on the standard output only the jobIds. Therefore any warning or info message is suppressed if this option is used.

--debug, -d

When this option is specified, debugging information is displayed on the standard output and written also into the file `glite-ce-job-list_CREAM_<username>_<date>_<time>.log` file under (by default) the `/tmp/glite_cream_cli_logs` directory.

--logfile file_name, -l file_name

When this option is specified, a command log file (whose pathname is `file_name`) is created.

--version, -v

Displays the version of the CREAM CLI software.

EXIT STATUS

`glite-ce-job-list` exits with a status value of 0 (zero) upon success, and >0 (greater than zero) upon failure.

EXAMPLES

```
> glite-ce-job-list cream-ce-01.pd.infn.it:8443
```

If the operation succeeded, the output will be a list of jobid, e.g:

```
https://cream-ce-01.pd.infn.it:8443/CREAM116j8te4j
```

```
https://cream-ce-01.pd.infn.it:8443/CREAM116j8uojl
```

```
https://cream-ce-01.pd.infn.it:8443/CREAM116j92f39
```

```
https://cream-ce-01.pd.infn.it:8443/CREAM116j93te1
```

```
https://cream-ce-01.pd.infn.it:8443/CREAM116j9403v
```

```
https://cream-ce-01.pd.infn.it:8443/CREAM116j942oc
```

```
https://cream-ce-01.pd.infn.it:8443/CREAM116j9457d
```

SEE ALSO

`glite-ce-job-submit`, `glite-ce-job-status`

Index

NAME

SYNOPSIS

DESCRIPTION

OPTIONS

OPTIONS

EXIT STATUS

EXAMPLES

SEE ALSO

This document was created by man2html, using the manual pages.

Time: 14:12:43 GMT, May 02, 2011

-- MassimoSgaravatto - 2011-05-02

This topic: CREAM > GliteCeJobList

Topic revision: r2 - 2013-06-06 - AlviseDorigo



Copyright © 2008-2022 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

Ideas, requests, problems regarding TWiki? Send feedback