

Table of Contents

glite-ce-job-output	1
NAME.....	1
SYNOPSIS.....	1
DESCRIPTION.....	1
OPTIONS.....	1
EXIT STATUS.....	2
EXAMPLES.....	2
SEE ALSO.....	2
Index.....	2

glite-ce-job-output

Section: User Commands (1)

Index

NAME

glite-ce-job-output - Retrieves the output sandbox files of one or more CREAM jobs.

SYNOPSIS

glite-ce-job-output [options] <jobId1> <jobId2> ... <jobIdn>

DESCRIPTION

The command `glite-ce-job-output` retrieves the output sandbox (OSB) files of CREAM jobs from CREAM CEs, in the scenario where the user asked to save these files in the CREAM CE (i.e. specifying `outputsandboxbasedesturi="gsiftp://localhost"`; in the JDL).

`glite-ce-job-output` can be used for one or more jobs: the jobs are identified by their job identifiers (job Ids returned by the `glite-ce-job-submit` command) provided as arguments to the command and separated by a blank space.

The `--input` option permits to specify a file (`file_name`) that contains the jobIds to be considered. This file must be the one generated with the `--output` option of the `glite-ce-job-submit` or `glite-ce-job-list` commands. If the file `file_name` does not represent an absolute path the file will be searched in the current working directory.

The OSB files of a job are retrieved and saved in a directory which is by default created in the current working directory (unless the `--dir` option is used).

OPTIONS

--help, -h

Displays command usage.

--conf file_name, -c file_name

Specifies the user specific configuration file.

--dir directory_name, -D directory_name

Specifies the parent directory where to create the job directory where the OSB files for that job will be saved

--num-streams number, -s number

Specifies the number of parallel streams to be used in the gridftp file transfer used in the OSB retrieval

--donot-verify-ac-sign, -A

Allows the execution of the command even if the VO voms server certificate is not installed.

--input file_name, -i file_name

Retrieves the OSB files of jobs whose Ids are contained in the file file_name.

--noint, -N

If this option is specified every interactive question to the user is skipped, and default values (yes; all: consider all jobs of the given list) will be considered.

--nomsg, -n

When this option is specified, any warning or info message is suppressed.

--debug, -d

When this option is specified, debugging information is displayed on the standard output and written also into the file glite-ce-job-output_CREAM_<username>_<date>_<time>.log file under (by default) the /tmp/glite_cream_cli_logs directory.

--logfile file_name, -l file_name

When this option is specified, a command log file (whose pathname is file_name) is created.

--version, -v

Displays the version of the CREAM CLI software.

EXIT STATUS

glite-ce-job-output exits with a value of 0 if the operation succeeds, >0 if errors occurred.

EXAMPLES

glite-ce-job-output https://cream-18.pd.infn.it:8443/CREAM753062965

glite-ce-job-output --input joblist.txt
where joblist.txt is a file containing jobIds

SEE ALSO

glite-ce-job-submit, glite-ce-job-list

Index

NAME
SYNOPSIS
DESCRIPTION
OPTIONS
EXIT STATUS
EXAMPLES
SEE ALSO

This document was created by man2html, using the manual pages.

Time: 10:55:39 GMT, May 05, 2011

-- MassimoSgaravatto - 2011-05-05

This topic: CREAM > GliteCeJobOutputMan

Topic revision: r1 - 2011-05-05 - MassimoSgaravatto



Copyright © 2008-2023 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

Ideas, requests, problems regarding TWiki? Send feedback