

-- AlessandroPaolini - 2011-09-30

### What have I to do to move the site-bdii on another machine?

1. be sure the new site-bdii is working and publishing all the necessary site information
2. put the old site-bdii in scheduled downtime on GOC-DB for a couple of hours
3. register the new service on GOC-DB by adding a new Service Endpoint:
  1. select "Site-BDII" in "Service Type" field
  2. fill in at least the hostname
  3. select "Y" for production and monitoring, "N" for beta service field
4. properly modify the "Giis Url" with the new *SITE-BDII ldap url*
5. mark the old site-bdii as not production and turn off its monitoring
6. top-BDIIs updates their sites-list every hour so the new site-bdii should be published in less than an hour; instead nagios updates the monitored host every 3 hours
7. when the new site-bdii is appeared on nagios and the old one is disappeared, turn off the old site-bdii and remove it from GOC-DB

### What if I have just to turn off a site-bdii cohosted with an lcg-CE:

1. yum remove glite-BDII glite-yaim-bdii
2. service bdii stop
3. delete some info-providers and ldif file:
  1. rm /opt/glite/etc/gip/ldif/stub-site.ldif
  2. rm /opt/glite/etc/gip/site-urls.conf
  3. rm /opt/glite/etc/gip/provider/glite-info-provider-site
  4. rm /opt/glite/etc/gip/provider/glite-info-provider-service-bdii-site-wrapper
  5. rm /opt/glite/etc/gip/ldif/glite-info-site.ldif
4. reconfigure with yaim without specifying the BDII\_site profile

back to <http://wiki.italiangrid.org/twiki/bin/view/Sandbox/HowTOs>

---

This topic: Sandbox > SiteBdiiChange

Topic revision: r4 - 2012-01-20 - AlessandroPaolini



Copyright © 2008-2023 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

Ideas, requests, problems regarding TWiki? Send feedback