

ApelSsmCfg < SiteAdminCorner < TWiki

```
]# less /etc/apel/sender.cfg
#####
# Required: broker configuration options
#

[broker]

# The SSM will query a BDII to find brokers available.  These details are for the
# EGI production broker network
bdii: ldap://egee-bdii.cnaf.infn.it:2170
network: PROD
# OR (these details will only be used if the broker network settings aren't used)
#host: test-msg01.afroditi.hellasgrid.gr
#port: 6163

# broker authentication.  If use_ssl is set, the certificates configured
# in the mandatory [certificates] section will be used.
use_ssl: true

#####
# Required: Certificate configuration

[certificates]
certificate: /etc/grid-security/hostcert.pem
key: /etc/grid-security/hostkey.pem
capath: /etc/grid-security/certificates
# If this is supplied, outgoing messages will be encrypted
# using this certificate
#server_cert: /etc/grid-security/servercert.pem

#####
# Messaging configuration.
#
[messaging]

# Queue to which SSM will send messages (use this)
destination: /queue/global.accounting.cpu.central

# Outgoing messages will be read and removed from this directory.
path: /var/spool/apel/outgoing

[logging]
logfile: /var/log/apel/ssmsend.log
# Available logging levels:
# DEBUG, INFO, WARN, ERROR, CRITICAL
level: INFO
console: true
```

-- AlessandroPaolini - 2014-06-13

This topic: SiteAdminCorner > ApelSsmCfg
Topic revision: r2 - 2014-09-17 - AlessandroPaolini



Copyright © 2008-2020 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

Ideas, requests, problems regarding TWiki? Send feedback