

CGISessionIDIncrDotPm < TWiki < TWiki

---+ Package == **extends** CGI::Session::ErrorHandler

=head1 NAME

CGI::Session::ID::incr - CGI::Session ID driver

=head1 SYNOPSIS

```
use CGI::Session; $session = new CGI::Session("id:Incr", undef, { Directory => '/tmp', IDFile =>
'/tmp/cgisession.id', IDInit => 1000, IDIncr => 2 });
```

=head1 DESCRIPTION

CGI::Session::ID::incr is to generate auto incrementing Session IDs. Compare it with L<CGI::Session::ID::md5|CGI::Session::ID::md5>, where session ids are truly random 32 character long strings. CGI::Session::ID::incr expects the following arguments passed to CGI::Session->new() as the third argument.

=over 4

=item IDFile

Location where auto incremented IDs are stored. This attribute is required.

=item IDInit

Initial value of the ID if it's the first ID to be generated. For example, if you want the ID numbers to start with 1000 as opposed to 0, that's where you should set your value. Default is C.

=item IDIncr

How many digits each number should increment by. For example, if you want the first generated id to start with 1000, and each subsequent id to increment by 10, set I to 10 and I to 1000. Default is C.

=back

=head1 LICENSING

For support and licensing information see L<CGI::Session|CGI::Session>

This topic: TWiki > CGISessionIDIncrDotPm

Topic revision: r1 - 2008-01-22 - TWikiContributor



Copyright © 1999-2019 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

Ideas, requests, problems regarding TWiki? Send feedback

Note: Please contribute updates to this topic on TWiki.org at TWiki:TWiki.CGISessionIDIncrDotPm.