

---+ Package ==

=head1 NAME

CGI::Session::Serialize::default - Default CGI::Session serializer

=head1 DESCRIPTION

This library is used by CGI::Session driver to serialize session data before storing it in disk.

All the methods are called as class methods.

=head1 METHODS

=over 4

=item freeze(\$class, \%hash)

Receives two arguments. First is the class name, the second is the data to be serialized. Should return serialized string on success, undef on failure. Error message should be set using `C<set_error()|CGI::Session::ErrorHandler/"set_error()"`>

=item thaw(\$class, \$string)

Received two arguments. First is the class name, second is the I data string. Should return thawed data structure on success, undef on failure. Error message should be set using `C<set_error()|CGI::Session::ErrorHandler/"set_error()"`>

=back

=head1 LICENSING

For support and licensing see [L<CGI::Session|CGI::Session>](#)

This topic: [TWiki > CGISessionSerializeDefaultDotPm](#)

Topic revision: r1 - 2008-01-22 - [TWikiContributor](#)



Copyright © 1999-2021 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

Ideas, requests, problems regarding TWiki? Send feedback

Note: Please contribute updates to this topic on [TWiki.org](#) at [TWiki:TWiki.CGISessionSerializeDefaultDotPm](#).