

---+ Package TWiki::UI::Edit

Edit command handler

StaticMethod edit (\$session)

Edit command handler. This method is designed to be invoked via the `UI::run` method. Most parameters are in the CGI query:

<code>cmd</code>	Undocumented save command, passed on to save script
<code>onlywikiname</code>	if defined, requires a wiki name for the topic name if this is a new topic
<code>onlynewtopic</code>	if defined, and the topic exists, then moans
<code>formtemplate</code>	name of the form for the topic; will replace existing form
<code>templatetopic</code>	name of the topic to copy if creating a new topic
<code>skin</code>	skin(s) to use
<code>topicparent</code>	name of parent topic (optional), undocumented <code>parenttopic</code> parameter can be used as well
<code>text</code>	text that will replace the old topic text if a <code>formtemplate</code> is defined (what the heck is this for?)
<code>contenttype</code>	optional parameter that defines the application type to write into the CGI header. Defaults to <code>text/html</code> .
<code>action</code>	Optional. If supplied, use the <code>edit\${action}</code> template instead of the standard edit template. An empty value means edit both form and text, "form" means edit form only, "text" means edit text only

This topic: TWiki > TWikiUIEditDotPm

Topic revision: r4 - 2011-04-12 - TWikiContributor



Copyright © 1999-2020 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

Ideas, requests, problems regarding TWiki? Send feedback

Note: Please contribute updates to this topic on TWiki.org at `TWiki:TWiki.TWikiUIEditDotPm`.