

----+ Package TWiki::Users::HtPasswdUser

Support for htpasswd and htdigest format password files.

Subclass of `TWiki::Users::Password`. See documentation of that class for descriptions of the methods of this class.

## ObjectMethod `finish ()`

Break circular references.

## ObjectMethod `readOnly () -> boolean`

returns true if the password file is not currently modifiable

## ObjectMethod `getMustChangePassword ($cUID) -> $flag`

Returns 1 if the \$cUID must change the password, else 0. Returns undef if \$cUID not found.

## ObjectMethod `getUserData ($cUID) -> $dataRef`

Return a reference to an array of hashes with user data, used to manage users. Each item is a hash with:

- `{name}` - name of field, such as "email"
- `{title}` - title of field, such as "E-mail"
- `{value}` - value of field, such as "jimmy@example.com"
- `{type}` - type of field: text, password, checkbox, label
- `{size}` - size of field, such as 40
- `{note}` - comment note, if any

User management forms can be build dynamically from this data structure. Each password manager may return a different set of fields.

## ObjectMethod `setUserData ($cUID, $dataRef)`

Set the user data of a user. Same array of hashes as `getUserData` is assumed, although only `{name}` and `{value}` are used.

Returns an empty string if save action is OK, or an error string starting with 'Error: ' if there is an error.

---

This topic: TWiki > TWikiUsersHtPasswdUserDotPm

Topic revision: r2 - 2011-08-21 - TWikiContributor



Copyright © 1999-2019 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

Ideas, requests, problems regarding TWiki? Send feedback

**Note:** Please contribute updates to this topic on TWiki.org at [TWiki.TWikiUsersHtPasswdUserDotPm](http://TWiki.TWikiUsersHtPasswdUserDotPm).