

QUERYPARAMS -- show paramaters to the query

- Expands the parameters to the query that was used to display the page.
- **Syntax:** %QUERYPARAMS{...}%
- **Parameters:**
 - ◆ `format="..."` format string for each entry, default `$name=$value`
 - ◆ `separator="..."` separator string, default `separator="$n"` (newline)
 - ◆ `encode="..."` the encoding to apply to parameter values; see ENCODE for a description of the available encodings. If this parameter is not given, no encoding is performed.
- The following escape sequences are expanded in the format string:

Sequence:	Expands To:
<code>\$name</code>	Name of the parameter
<code>\$value</code>	String value of the parameter. Multi-valued parameters will have a "row" for each value.
<code>\$n</code> or <code>\$n()</code>	New line. Use <code>\$n()</code> if followed by alphanumeric character, e.g. write <code>Foo\$n()Bar</code> instead of <code>Foo\$nBar</code>
<code>\$nop</code> or <code>\$nop()</code>	Is a "no operation". This variable gets removed; useful for nested search
<code>\$quot</code>	Double quote (") (\\" also works)
<code>\$percent</code>	Percent sign (%)
<code>\$dollar</code>	Dollar sign (\$)
<code>\$lt</code>	Less than sign (<)
<code>\$gt</code>	Greater than sign (>)

- **Example:** %QUERYPARAMS{format="<input type='hidden' name='\$name' value='\$value' encoding="html" />"}%
- See also QUERYSTRING, URLPARAM

This topic: TWiki > VarQUERYPARAMS

Topic revision: r5 - 2011-06-14 - TWikiContributor



Copyright © 1999-2022 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

Ideas, requests, problems regarding TWiki? Send feedback

Note: Please contribute updates to this topic on TWiki.org at TWiki:TWiki.VarQUERYPARAMS.