

## SESSION\_VARIABLE -- get, set or clear a session variable

- Session variables are stored in a personal "persistent memory space" that is not lost until the web browser is closed
  - Syntax: %SESSION\_VARIABLE{"name"}% - read a session variable
  - Syntax: %SESSION\_VARIABLE{"name" set="value"}% - set a session variable
  - Syntax: %SESSION\_VARIABLE{"name" clear=""}% - clear a session variable
  - Special read-only session variables:
    - ◆ %SESSION\_VARIABLE{"AUTHUSER"}% - user ID, current value:
    - ◆ %SESSION\_VARIABLE{"SESSION\_REQUEST\_NUMBER"}% - number of pages accessed by current user since login, current value:
  - Related: TWikiUserAuthentication#Sessions, AUTHREALM, GET, LOGIN, LOGOUT, SESSIONID, SESSIONVAR, SET
- 

This topic: TWiki > VarSESSIONVARIABLE

Topic revision: r3 - 2011-04-09 - TWikiContributor



Copyright © 1999-2023 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

Ideas, requests, problems regarding TWiki? Send feedback

**Note:** Please contribute updates to this topic on TWiki.org at TWiki:TWiki.VarSESSIONVARIABLE.