


Help on Preferences

- A preference setting is defined by:
3 or 6 spaces * Set NAME = value
Example:
 - ◆ Set WEBBGCOLOR = #FFFFC0
- A preferences setting can be disabled with a # sign. Remove the # sign to enable a local customisation. Example:
 - ◆ #Set DENYWEBCHANGE = UnknownUser
- Preferences are used as TWikiVariables by enclosing the name in percent signs. Example:
 - ◆ When you write variable %WEBBGCOLOR% , it gets expanded to #FFD8AA
- The sequential order of the preference settings is significant. Define preferences that use other preferences first, i.e. set WEBCOPYRIGHT before WIKIWEBMASTER since %WEBCOPYRIGHT% uses the %WIKIWEBMASTER% variable.
- You can introduce your own preferences variables and use them in your topics and templates.

Related Topics

- TWiki.TWikiPreferences, Main.TWikiPreferences - site-level preferences
- UserList - list of user topics. User topics can have optional user preferences
- TWikiVariables - list of common %VARIABLES%
- TWikiAccessControl - explains how to restrict access by users or groups

Tools

-  **Rename, move or delete this web:**
 - ◆ *Note:* The TWiki web cannot be renamed. See also: ManagingWebs

This topic: TWiki > WebPreferencesHelp

Topic revision: r5 - 2011-07-29 - TWikiContributor



Copyright © 1999-2022 by the contributing authors. All material on this collaboration platform is the property of the contributing authors.

Ideas, requests, problems regarding TWiki? Send feedback

Note: Please contribute updates to this topic on TWiki.org at TWiki:TWiki.WebPreferencesHelp.